

# STREET-LITE (LED-2)

Stand-alone, self-powered solar lighting tower



When looking for a portable, easy to manage solar lighting tower, look no further than our Street-Lite (LED-2).















Suitable for low level lighting applications only, such as car parks, walkways, steps or stairs.

### **Features**

1 x 40W + 1 x 15W fully adjustable 360° swivel & tilt LED lighting head complete with fully automatic PIR motion sensor

An MHM Dusk 'til Dawn Auto on/off sensor

5.5m vertical stainless steel manual mast

High efficiency & fully tiltable solar panel

Heavy duty, deep cycle battery

On/Off switch

Battery charge level indicator

Built in 230V mains charger c/w 13A plug & lead

Central lifting eye and front, side and rear fork pockets

### Benefits

15W LED light on at all times at night & 40W LED light will automatically turn on and off when activity is near or far, saving power

Light will automatically turn on/off as per sunset and sunrise – when in Auto mode only

For quick, simple and easy set-up

Harvesting solar energy in all UK seasons and weather conditions

Ample power to support most low level site lighting applications all year round with no other power support or back up power required

Turn light off when in transport or storage

Quick, simple and easy visual check of the battery charge status on and

Have light fully charged and ready for hire at all times when stored inside depot, plugged in to mains power

For flexible and safe loading and off-loading











## **STREET-LITE** (LED-2)











# Specification

**Dimensions** (Storage mode, mast down & solar panel flat – "horizontal")

Length: 1500 mm Width: 760 mm Height: 2100 mm **Dimensions** (Operation mode, mast up & solar panel tilted) Width: 760 mm Height: 5500 mm Weight: 280 kg

#### **Performance**

1 x 175W Solar Panel Battery Runtime (1 x Full Charge) Max. Light (Bright – 2 x LED on) 13 Hours Min. Light (Dim  $-1 \times LED$  on) Mechanical Protection - IP AGM Sealed Lead Acid Expected Battery Cycle 500 CO2 Output Per Hour 'All Lights On'

#### Lighting

Light Coverage	400m <sup>2</sup>
Lighting Head	1 x 15W LED on at all times + 1 x 40W LED turns on when activated by PIR motion sensor
Max Mast Height	5.5m
Mast Type	Manual
Certified Wind Sta	ability 110kmh / 70mph



The zero CO<sub>2</sub> emissions and zero fuel usage achieved by contractors when hiring Street-Lite Lighting Towers can be included in the Contractors Sustainability Policy, which will help them to win Government and Local Authority Contracts.

For more details call MHM TODAY

on **0808 168 9099** 

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk











